

HANDLESETS

Door Prep	Deadbolt: Cross Bore 2-1/8" or 1-1/2" Edge Bore 1" Latch Face 1" x 2-1/4".
	Handle: Cross Bore 2-1/8". Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Deadbolt: Adjustable to 2-3/8" or 2-3/4" Handle: Adjustable to 2-3/8" or 2-3/4"
Door Thickness	1-3/4" doors standard. 2-1/4" doors optional.
Cylinder	SmartKey or KW 5pin
Faceplate	1" x 2-1/4". Specify round corner or square corner or drive-in.

Strikes	Deadbolt: 1-1/8" x 2-3/4" Specify round corner or square corner Handle: 2-1/4" full lip Specify round corner or square corner Other options available
Bolt	Deadbolt: 1" steel Handle: 1/2" throw. Nickel plated.
Door Handing	Reversible for right or left-hand doors.
ANSI/BHMA	A156.5 Grade 1 (for deadbolt).
ADA	N/A
UL	N/A

LEVERS

Door Prep	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional
Door Thickness	1-3/8" - 1-3/4" doors standard. 2-1/4" doors optional on GCL 331 and GCL 535
Cylinder	SmartKey or KW 5pin
Faceplate	1" x 2-1/4" Specify round corner, square corner or drive-in.

Strikes	2-1/4" full lip. Specify round corner or square corner. Other options available.
Bolt	1/2" throw nickel plated.
Door Handing	Specify handing only with Inactive levers
ANSI/BHMA	A156.2 Grade 2.
ADA	Functions GCL 101, GCL 12 satisfies section 4.13.9 ADA requirement.
UL	Meets 3 hour fire rating for all UL functions when fronted latches used. Meets 20 minute with drive-in latch.

KNOBS

Door Prep	Cross Bore: 2-1/8" Edge Bore: 1" Latch Face: 1" x 2-1/4".
Backset	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional
Door Thickness	1-3/8" - 1-3/4" doors standard. 2-1/4" doors optional. 2-1/4" doors optional on GCA 101 and GCA 531 models only.
Cylinder	SmartKey or KW 5pin.
Faceplate	1" x 2-1/4". Specify round corner, square corner or drive-in.

Strikes	2-1/4" full lip. Specify round corner or square corner. Other options available.
Bolt	1/2" throw nickel plated
Door Handing	Reversible for right- or left-hand doors.
ANSI/BHMA	A156.2 Grade 2.
ADA	N/A
UL	Meets 3 hour fire rating for all UL functions when fronted latches used. Meets 20 minute with drive-in latch.

DEADBOLTS

Door Prep	Crossbore 2-1/8" or 1-1/2" Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Adjustable to 2-3/8" or 2-3/4"
Door Thickness	SMT 1-3/8" - 1-3/4" KW P&T 1-3/4"
Cylinder	SmartKey or KW 5pin
Faceplate	1" x 2-1/4". Specify round corner, square corner or drive-in.

Strikes	Standard: Grade 1, 1-1/8" x 2-3/4" Specify round corner or square corner. Other options available.
Bolt	1" throw Steel.
Door Handing	Reversible for right or left-hand doors.
ANSI/BHMA	A156.5 Grade 1.
ADA	Interior turn piece meets 4.13.9 ADA requirements.
UL	Meets 3 hour fire rating for all UL functions when fronted latches used. Meets 20 minute with drive-in latch.

KEY CONTROL DEADBOLT

Door Prep	Crossbore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"
Door Thickness	1-3/8" - 1-3/4"
Cylinder	2 SmartKey cylinders: 1 Standard SmartKey for users. 1 Secure new patented keyway for Key Control.
Faceplate	1" x 2-1/4".

Strikes	1-1/8" x 2-3/4"
Bolt	1" throw.
ANSI/BHMA	A156.5 Grade 2.
ADA	Interior turn piece meets 4.13.9 ADA requirements.
UL	Meets 3 hour fire rating for all UL functions when fronted latches used. ULRef#R10923. Meets 20 minute with drive-in latch..