

HANDLESETS

Door Prep	Deadbolt: Cross Bore 2-1/8" or 1-1/2" Edge Bore 1" Latch Face 1" x 2-1/4"
	Handle: Cross Bore 2-1/8". Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Deadbolt: Adjustable to 2-3/8" or 2-3/4" Handle: Adjustable to 2-3/8" or 2-3/4"
Door Thickness	1-3/4" doors standard. 2-1/4" doors optional
Cylinder	SmartKey or KW or WS 5 pin
Faceplate	1" x 2-1/4" Specify round corner or square corner or drive-in

Strikes	Deadbolt: 1-1/8" x 2-3/4" Specify round corner or square corner Handle: 2-1/4" full lip Specify round corner or square corner Other options available
Bolt	Deadbolt: 1" Handle: 1/2" throw
Door Handing	Reversible for right or left-hand doors
ANSI/BHMA	A156.5 Grade 3 Deadbolt
ADA	N/A
UL	N/A

LEVERS

Door Prep	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional
Door Thickness	1-3/8" - 1-3/4" doors standard.
Cylinder	2-1/4" doors optional on GLC 101 models KW or WS 5 pin
Faceplate	1" x 2-1/4" Specify round corner, square corner or drive-in

Strikes	2-1/4" full lip Specify round corner or square corner Other options available
Bolt	1/2" throw nickel plated
ANSI/BHMA	A156.2 Grade 3
ADA	Functions GLC 101 and GLC 12 satisfy section 4.13.9 ADA requirement
UL	Meets 20 minute fire rating for UL functions

KNOBS

Door Prep	Cross Bore: 2-1/8" Edge Bore: 1" Latch Face: 1" x 2-1/4".
Backset	Adjustable to 2-3/8" or 2-3/4". UL 2-3/4" standard 2-3/8" optional.
Door Thickness	1-3/8" - 1-3/4" doors standard.
Cylinder	2-1/4" doors optional on GAC 101 models only. KW or WS 5 pin
Faceplate	1" x 2-1/4". Specify round corner, square corner or drive-in.

Strikes	2-1/4" full lip. Specify round corner or square corner. Other options available.
Bolt	1/2" throw nickel plated
Door Handing	Reversible for right- or left-hand doors.
ANSI/BHMA	A156.2 Grade 3
ADA	N/A
UL	Meets 20 minute fire rating for UL function

DEADBOLTS

Door Prep	Crossbore 1-1/2" Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional
Door Thickness	1-3/8" - 1-3/4" Standard
Cylinder	SmartKey or KW or WS 5 pin
Faceplate	1" x 2-1/4" Specify round corner, square corner or drive-in

Strikes	Standard: 1-1/8" x 2-3/4" Specify round corner or square corner
Bolt	1" throw
Door Handing	Reversible for right or left-hand doors
ANSI/BHMA	A156.5 Grade 3
ADA	Interior turn piece meets 4.13.9 ADA requirements
UL	Meets 20 minute fire rating for UL function

NOTE: Elements does not meet grade 3 when installed on a 2-1/8" crossbore