

HANDLESETS

Door Prep	Deadbolt: Cross Bore 2-1/8" or 1-1/2" Edge Bore 1" Latch Face 1" x 2-1/4".
	Handle: Cross Bore 2-1/8". Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Deadbolt: Adjustable to 2-3/8" or 2-3/4" Handle: Adjustable to 2-3/8" or 2-3/4"
Door Thickness	1-3/4" doors standard. 2-1/4" doors optional.
Cylinder	SmartKey or KW 5pin
Faceplate	1" x 2-1/4". Specify round corner or square corner or drive-in.

Strikes	Deadbolt: 1-1/8" x 2-3/4" Specify round corner or square corner Handle: 2-1/4" full lip Specify round corner or square corner Other options available
----------------	---

Bolt	Deadbolt: 1" steel Handle: 1/2" throw. Nickel plated.
-------------	--

Door Handing Reversible for right or left-hand doors.

ANSI/BHMA A156.5 Grade 1 (for deadbolt).

ADA N/A

UL N/A

LEVERS

Door Prep	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional
Door Thickness	1-3/8" - 1-3/4" doors standard.
Cylinder	SmartKey or KW 5pin
Faceplate	1" x 2-1/4" Specify round corner, square corner or drive-in.

Strikes	2-1/4" full lip. Specify round corner or square corner. Other options available.
----------------	--

Bolt	1/2" throw nickel plated.
-------------	---------------------------

Door Handing Specify handing only with Inactive levers

ANSI/BHMA A156.2 Grade 2.

ADA Functions GCL 101, GCL 12 satisfies section 4.13.9 ADA requirement.

UL Meets 3 hour fire rating for all UL functions when fronted latches used.
Meets 20 minute with drive-in latch.

KNOBS

Door Prep	Cross Bore: 2-1/8" Edge Bore: 1" Latch Face: 1" x 2-1/4".
Backset	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional
Door Thickness	1-3/8" - 1-3/4" doors standard. 2-1/4" doors optional.
Cylinder	SmartKey or KW 5pin.
Faceplate	1" x 2-1/4". Specify round corner, square corner or drive-in.

Strikes	2-1/4" full lip. Specify round corner or square corner. Other options available.
----------------	--

Bolt	1/2" throw nickel plated
-------------	--------------------------

Door Handing Reversible for right- or left-hand doors.

ANSI/BHMA A156.2 Grade 2.

ADA N/A

UL Meets 3 hour fire rating for all UL functions when fronted latches used.
Meets 20 minute with drive-in latch.

DEADBOLTS

Door Prep	Crossbore 2-1/8" or 1-1/2" Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	Adjustable to 2-3/8" or 2-3/4"
Door Thickness	SMT 1-3/8" - 1-3/4" KW P&T 1-3/4"
Cylinder	SmartKey or KW 5pin
Faceplate	1" x 2-1/4". Specify round corner, square corner or drive-in.

Strikes	Standard: Grade 1, 1-1/8" x 2-3/4" Specify round corner or square corner. Other options available.
----------------	--

Bolt	1" throw Steel.
-------------	-----------------

Door Handing Reversible for right or left-hand doors.

ANSI/BHMA A156.5 Grade 1.

ADA Interior turn piece meets 4.13.9 ADA requirements.

UL Meets 3 hour fire rating for all UL functions when fronted latches used.
Meets 20 minute with drive-in latch.